



深圳市天漠科技有限公司 液晶模块系列选型指南

产品型号	屏幕尺寸	外型尺寸mm2	分辨率	工作温度	存储温度	电气指标	支持底板类型
LCD2000-35T	3.5 Inch	111.5*71.0	320*240	-20~60° C	-30~80° C	3.3V 1W	SBC2410-III
LCD6000-35T	3.5 Inch	102.9*71.0	320*240	-20~60° C	-30~80° C	3.3V 1W	SBC6000X SBC9261-I
LCD2000-43T	4.3 Inch	120.2*80.0	480*272	-20~70° C	-30~80° C	5V 1W	SBC2410-III SBC2440-III
LCD6000-43T	4.3 Inch	120.2*80.0	480*272	-20~70° C	-30~80° C	5V 1W	SBC6000X SBC9261-I
LCD8000-43T	4.3 Inch	120.2*80.0	480*272	-20~70° C	-30~80° C	5V 1W	Devkit8000
LCD2000-56T	5.6 Inch	143.5*114.0	640*480	-20~70° C	-30~80° C	5V 2.5W	SBC2410-III SBC2440-III
LCD6000-56T	5.6 Inch	143.5*114.0	640*480	-20~70° C	-30~80° C	5V 2.5W	SBC6000X SBC9261-I
LCD8000-56T	5.6 Inch	143.5*114.0	640*480	-20~70° C	-30~80° C	5V 2.5W	Devkit8000
LCD2000-70T	7 Inch	181.0*120.0	800*480	-10~60° C	-20~70° C	5V 3.5W	SBC2440-III
LCD6000-70T	7 Inch	181.0*120.0	800*480	-10~60° C	-20~70° C	5V 3.5W	SBC6000X SBC9261-I
LCD8000-70T	7 Inch	181.0*120.0	800*480	-10~60° C	-20~70° C	5V 3.5W	Devkit8000

